

Slides #9
for Loop

CMPT 130
© Dr. B. Fraser

for

- Definite Loop:
 - A loop where we know ...

“Count from 1 to 10..”
- Indefinite Loop:
 - A loop where we...
tell how many times we will execute the loop:
“Count up from 1 to find first multiple of 3, 4 and 18”
- for loops are often useful to neatly organizing definite loops.

Simple Example

```
for (int i = 0; i < 5; i++) {  
    // Do amazing stuff here!  
    cout << "i: " << i << endl;  
}
```

Output:

```
i: 0  
i: 1  
i: 2  
i: 3  
i: 4
```

Above code identical to:

```
{  
    int i = 0;  
    while (i < 5) {  
        cout << "i: " << i << endl;  
        i++;  
    }  
}
```

Which is easier to read?

```
for (int i = 0; i < 5; i++) {  
    cout << "i: " << i << endl;  
}
```

```
{  
    int i = 0;  
    while (i < 5) {  
        cout << "i: " << i << endl;  
        i++;  
    }  
}
```


Work Through Examples

```
for (int i = 0; i < 12; i++) {  
    cout << "Month # " << i << endl;  
}
```

```
for (int i = 100; i > 0; i--) {  
    cout << i << endl  
}
```

```
for (int rows = 0; rows < 10; rows++) {  
    if (rows % 3 == 0) {  
        rows ++;  
    }  
    cout << rows;    ..  
}
```

```
for (int rows = 0; rows < 10; rows++) {  
    if (rows % 3 != 0) {  
        cout << rows;  
    }  
}
```



Notes on for

- Variables declared in the for loop's initialization...

```
for (int i = 0; i < 10; i++) {  
    cout << i << endl;  
}  
cout << i << endl;           //..
```

Exercise

- Convert this into a for loop:

```
int i = 0;
while (i < 10) {
    cout << i << endl;
    i++;
}
```

- Convert this into a while loop:

```
for (int j = 99; j > 0; j--) {
    cout << "# bottles: "
        << j << endl;
}
```

break and continue

- You can control loop execution inside the loop
 - break:...
 - continue:..
 - Will re-evaluate the condition, and keep looping.

```
int sum = 0;
while (true) {
    int val = 0;
    cout << "Enter a value: ";
    cin >> val;
    if (val < 0) {
        break;
    }
    sum += val;
}
```

- Don't use these often
 - They can complicate how the loops execute.
 - Can be useful for handling error conditions.

Practice Questions

- Write the following in both a for and while loop:
 - Print all multiples of 5 from 100 down to 0.

- Write a function which:
 - Accepts two numbers, m and n.
 - Returns the sum of all numbers between m and n (you may assume $m \leq n$)
 - Use a for-loop.

Summary

- Loops run code multiple times
 - while loop
Indefinite loop: good for running while a condition is true.
 - for loop
Definite loop: good for running a fixed number of times.
- Use either a while or for loop
 - for loops put all looping logic on one line.
 - while loops give you more customized control.